



D.ELECTRON
since 1977 hi-tech for machine tools

Spindle Motor MA IP54 D.Electron

Base Velocity [RPM]	Nominal Voltage [3xVca]	Power [KW/S1]	Motor type	Tn [Nm]	MAX Velocity [RPM]	In [ARMS]	Suited SPS Evo module	Suited power cable
750 (Star / Triangle)	360	8.5	MA 133K-E2	109	7000	23	35	n.a.
		13.5	MA 133M-E2	166	7000	36	50	n.a.
		16	MA 133P-E2	217	7000	45	50	n.a.
		21	MA 160M-E2	255	6000	50	50	n.a.
		25	MA 160L-EB	310	6000	61	80	n.a.
		35	MA 180M-EC	446	4500	85	100	n.a.
		44	MA 180P-E7	560	4500	110	140	n.a.
1000	360	2.5	MA 100S-E1	24	9000	6.9	10	D894
		4.1	MA 100M-E2	39	9000	11	20	D894
		5.7	MA 100L-E1	55	9000	15.6	20	D894
		7	MA 100P-E2	66	9000	19.4	20	D894
		11	MA 133K-E1	105	7000	27	35	D897
		15	MA 133S-E1	143	7000	36	35	D897
		21	MA 133P-E1	200	7000	51	50	D898
		28	MA 160M-E8	267	6000	58	80	D901
	400	33	MA 160L-E1	315	6000	73	80	D901
		35	MA 160P-E1	334	5000	81	80	D901
		46	MA 180M-EA	439	4500	85	100	D963
		57	MA 180P-E1	544	4500	107	140	D964
		67	MA 225S-EA	640	3500	125	140	n.a.
		94	MA 225L-EC	898	3500	178	200	n.a.
1500	360	3.7	MA 100S-F1	24	9000	10	10	D894
		6	MA 100M-F1	39	9000	15	20	D894
		8.2	MA 100L-F1	55	9000	21	20	D894
		10	MA 100P-F1	66	9000	25	35	D895
		16	MA 133K-F1	105	7000	38	50	D898
		21	MA 133S-F1	143	7000	48	50	D898
		24	MA 133M-F1	153	7000	54	80	D899
		30	MA 133P-F1	200	7000	68	80	D899
	400	40	MA 160M-F1	267	6000	82	100	D901
		45	MA 160L-FB	315	6000	84	100	D901
		49	MA 160P-FA	334	5000	93	100	D902
		64	MA 180M-FB	439	4500	123	140	n.a.
		80	MA 180P-EA	544	4500	149	200	n.a.
		93	MA 225S-FA	640	3500	178	200	n.a.

≅ Tolerance ± 8%

n.a. = not available

D.Electron srl - Via R. Giuliani 140 - 50141 Florence ITALY - www.delectron.it

All information contained herein have been accurately checked to be exact and reliable, however D.Electron doesn't assume any responsibility for possible inaccuracies. D.Electron reserves the right to make all modifications necessary to improve the performance and reliability of its products.